

EARTHMAX SR 43 - Tekniska specifikationer



Description

EARTHMAX SR 43 (L-4) är ett radialdäck helt i stål specialdesignat för hjullastare som körs i krävande, steniga miljöer, framför allt vid underjordisk gruvdrift. Däcket ger utmärkt prestanda vid lastning och transporter i daggruvor, stenbrott och skrotupplag. Det unika mönstret skapar överlägsen dragförmåga och stabilitet. Tack vare däckhöljet helt i stål ger EARTHMAX SR 43 (L-4) utmärkt hållbarhet, motståndskraft mot revor och punkteringar samt lång livslängd.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	229 A2

Dimensions US Standard

Usa code	94068869
Overall Width (inch)	35.4
Overall Diameter (inch)	81.7
Static Loaded Radius (inch)	37.7
Rolling Circumference (inch)	252.4
Rim Rec	28.00/3.5
Star Rating	***
TRA Code	L4

Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	64000	66000	68000	69500	70500	71500

Printed on 3/4/2024 4:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..