

EARTHMAX SR 43 - Ladda ned faktablad



Description

EARTHMAX SR 43 (L-4) är ett radialdäck helt i stål specialdesignat för hjullastare som körs i krävande, steniga miljöer, framför allt vid underjordisk gruvdrift. Däcket ger utmärkt prestanda vid lastning och transporter i daggruvor, stenbrott och skrotupplag. Det unika mönstret skapar överlägsen dragförmåga och stabilitet. Tack vare däckhöljet helt i stål ger EARTHMAX SR 43 (L-4) utmärkt hållbarhet, motståndskraft mot revor och punkteringar samt lång livslängd.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Hjullastare

| SIZE | Version | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|-----------------------------|------------------------------|----------|-----------|--------|-----------|----------------------|-----|------|-----|------|------|
| 29.5 R 25 | CUT RESISTANT COMPOUND | L4 | ** | 216 A2 | 25.00/3.5 | | 785 | 1875 | 847 | 5644 | TL |
| 29.5 R 25 | CUT RESISTANT COMPOUND | L4 | *** | 221 A2 | 25.00/3.5 | | 785 | 1875 | 847 | 5644 | TL |
| 29.5 R 29 | CUT RESISTANT COMPOUND | L4 | *** | 223 A2 | 25.00/3.5 | 24.00/3.5, 26.00/3.5 | 768 | 2003 | 905 | 6029 | TL |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | L4 | *** | 228 A2 | 27.00/3.5 | 27.00/3.0; 28.00/3.5 | 852 | 1877 | 844 | 5702 | TL |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L4 | ** | 224 A2 | 28.00/3.5 | | 900 | 2076 | 957 | 6412 | TL |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L4 | *** | 229 A2 | 28.00/3.5 | | 900 | 2076 | 957 | 6412 | TL |
| 35/65 R 33 | CUT RESISTANT COMPOUND | E4/L4 | ****/**** | | 28.00/3.5 | | 900 | 2076 | 957 | 6412 | TL |
| 35/65 R 33 | CUT RESISTANT COMPOUND (UMS) | E4 | **** | | 28.00/3.5 | | 900 | 2076 | 957 | 6412 | TL |

Printed on 2/21/2024 6:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..