

## EARTHMAX SR 44 - Tekniska specifikationer



### Description

EARTHMAX SR 44 (E-4) är ett stålradialdäck som passar en mängd olika användningsområden, till exempel i gruvor, vid vägtransporter och skogsavverkning. Det robusta E-4-slitbanemönstret ger både utmärkt dragkraft och hög komfort för föraren. EARTHMAX SR 44 (E-4) hjälper dig att optimera produktiviteten oberoende av användningsområde.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Väg- och terränggående lastbil

Version	STANDARD
Type	TT
Tyre Size	7.50 R 16
LI/SS	122/118 G

## Dimensions International Standard

Overall Width (mm)	226
Overall Diameter (mm)	820
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2450
Rim Rec	6
Rim Alt	5.5, 6.5

## Load capacity (Kg)

	km/h / bar	7.25
	90 LS	1500
	90 LD	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 3:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..