

## EARTHMAX SR 45 H2 - Tekniska specifikationer



### Description

EARTHMAX SR 45 H2 är ett radialdäck helt i stål som är särskilt konstruerat för anläggningsbilar. E-4-däckets mönsterdjup och den unika mönsterutformningen säkerställer utomordentlig slitstyrka och minimerar vibrationer och buller. EARTHMAX SR 45 H2 är idealiskt för all drift som kräver dragförmåga och stabilitet. Stålradiastommen ger utmärkt motståndskraft mot revor och punkteringar och lång livslängd. Däcket finns i standardutförande samt i sammansättningar med värme- och skärmotstånd.

### UM

US Standard

### Construction



RADIAL

### Machinery

OTR: Stel dumper

|           |                   |
|-----------|-------------------|
| Version   | STANDARD COMPOUND |
| Type      | TL                |
| Tyre Size | 24.00 R 35        |
| LI/SS     | 209 B             |

Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94059720  |
| TMPH                         | 267       |
| Overall Width (inch)         | 26        |
| Overall Diameter (inch)      | 85.8      |
| Static Loaded Radius (inch)  | 38.5      |
| Rolling Circumference (inch) | 259.7     |
| Rim Rec                      | 17.00/3.5 |
| Rim Alt                      | --        |
| Star Rating                  | **        |
| TRA Code                     | E4        |
| Tread Depth                  | 88        |

Load capacity (lbs)

|           |       |       |       |       |       |       |       |       |       |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| mph / psi | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
| 30        | 30900 | 32000 | 34200 | 35300 | 36400 | 37500 | 38600 | 39700 | 40800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 2:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..