

EARTHMAX SR 45 H2 - Tekniska specifikationer



Description

EARTHMAX SR 45 H2 är ett radialdäck helt i stål som är särskilt konstruerat för anläggningsbilar. E-4-däckets mönsterdjup och den unika mönsterutformningen säkerställer utomordentlig slitstyrka och minimerar vibrationer och buller. EARTHMAX SR 45 H2 är idealiskt för all drift som kräver dragförmåga och stabilitet. Stålradialstommen ger utmärkt motståndskraft mot revor och punkteringar och lång livslängd. Däcket finns i standardutförande samt i sammansättningar med värme- och skärmotstånd.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	212 B

Dimensions International Standard

TKPH	435
Overall Width (mm)	660
Overall Diameter (mm)	2180
Static Loaded Radius (mm)	978
Rolling Circumference (mm)	6597
Rim Rec	17.00/3.5
Rim Alt	---
Star Rating	***
TRA Code	E4
Tread Depth	70

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	19000	19250	19500	20000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 3:04 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..