

# EARTHMAX SR 45 H2 - Tekniska specifikationer



## Description

EARTHMAX SR 45 H2 är ett radaldäck helt i stål som är särskilt konstruerat för anläggningsbilar. E-4-däckets mönsterdjup och den unika mönsterutformningen säkerställer utomordentlig slitstyrka och minimerar vibrationer och buller. EARTHMAX SR 45 H2 är idealiskt för all drift som kräver dragförmåga och stabilitet. Stålradialstommen ger utmärkt motståndskraft mot revor och punkteringar och lång livslängd. Däcket finns i standardutförande samt i sammansättningar med värme- och skärmotstånd.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Stel dumper

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	212 B

## Dimensions US Standard

Usa code	94063826
TMPH	298
Overall Width (inch)	26
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.5
Rolling Circumference (inch)	259.7
Rim Rec	17.00/3.5
Rim Alt	---
Star Rating	***
TRA Code	E4
Tread Depth	88

## Load capacity (lbs)

mph / psi	105	109	112	116
30	41900	42500	43000	44100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 2:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..