

## EARTHMAX SR 45 PLUS - Tekniska specifikationer



### Description

EARTHMAX SR 45 PLUS är ett stålradialdäck för gruvtruckar. Det är idealiskt för längre transporter. EARTHMAX SR 45 PLUS har ett slitbanemönster som minimerar vibrationer och buller.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

## Dimensions US Standard

Usa code	94045655
TMPH	301
Overall Width (inch)	29.4
Overall Diameter (inch)	106.4
Static Loaded Radius (inch)	47.8
Rolling Circumference (inch)	318.7
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Printed on 4/27/2024 5:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..