

EARTHMAX SR 452 - Ladda ned faktablad



Description

EARTHMAX SR 452 är ett radialdäck helt i stål som utformats speciellt för styva dumprar som används till transport.

Dess unika E-4-slitbanemönster är utformat för att garantera utmärkt dragkraft och exceptionell dragförmåga mot värme, vilket minimerar vibrationer och ljud för att garantera hantering och komfort.

Dess starka stålhölje och däckbälten ger utmärkt stabilitet och motståndskraft mot snitt och punkteringar.

EARTHMAX SR 452 har utvecklats med en kvadratisk axel som maximerar markkontakten för utmärkt manövrerbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		660	2170	995	6729	TL	355
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5		660	2170	995	6729	TL	355
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5		660	2170	995	6729	TL	415
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5		660	2170	995	6729	TL	415

Printed on 4/26/2024 7:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..