

EARTHMAX SR 46 - Ladda ned faktablad



Description

Earthmax SR 46 för gruvtruckar är BKT:s innovativa svar när det gäller användning i tuffa och nötande gruvmiljöer med mycket sten. Det här däckets är designat för att kunna hantera tunga laster, vara utomordentligt tåligt mot skär- och skrapskador och ha en lång livscykel. Det stålförstärkta höljet och stålbalterna ger ett utomordentligt skydd mot stötar, utmattning och punkteringar för att maximera drifttiden och öka produktiviteten. Earthmax SR 46 har ett särskilt blockmönster med periferiska spår för att optimera däckets prestanda vid kurvtagning och minimera skadorna på mönsterytan.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
27.00 R 49	CUT RESISTANT COMPOUND	94050161	E4	**	223 B	19.50/4.0	-	29.4	105.8	48.2	321.5	TL	312
27.00 R 49	HEAT RESISTANT COMPOUND	94055159	E4	**	223 B	19.50/4.0	-	29.4	105.8	48.2	321.5	TL	449
27.00 R 49	STANDARD COMPOUND	94050178	E4	**	223 B	19.50/4.0	-	29.4	105.8	48.2	321.5	TL	404
30.00 R 51	CUT RESISTANT COMPOUND	94074747	E4	**	230 B	22.00/4.5		32.9	114	51.2	346.5	TL	342
30.00 R 51	HEAT RESISTANT COMPOUND	94074723	E4	**	230 B	22.00/4.5		32.9	114	51.2	346.5	TL	497
30.00 R 51	STANDARD COMPOUND	94074754	E4	**	230 B	22.00/4.5		32.9	114	51.2	346.5	TL	418
33.00 R 51	CUT RESISTANT COMPOUND	94061723	E4	**	235 B	24.00/5.0		35.6	120.1	55.2	369.2	TL	382
33.00 R 51	HEAT RESISTANT COMPOUND	94067350	E4	**	235 B	24.00/5.0		35.6	120.1	55.2	369.2	TL	548
33.00 R 51	STANDARD COMPOUND	94065240	E4	**	235 B	24.00/5.0		35.6	120.1	55.2	369.2	TL	477

Printed on 4/27/2024 6:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..