

EARTHMAX SR 475 - Tekniska specifikationer



Description

EARTHMAX SR 475 är ett radialdäck helt i stål som är särskilt konstruerat för långtradare utan midjestyning. Det passar perfekt till hårda och steniga underlag, i synnerhet vid långa transporter. Det unika däckmönstret genererar mindre värme i varma klimat och erbjuder utmärkt dragförmåga. Den kraftfulla stålradialstommen med stålbalten ger imponerande stabilitet och motståndskraft mot revor och punkteringar. EARTHMAX SR 475 är konstruerat med en fyrkantig däcksuldra som säkerställer utmärkt manövreringsförmåga och hantering samt maximerar kontakten med underlaget.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	191 B

Dimensions US Standard

Usa code	94064397
TMPH	182
Overall Width (inch)	19.3
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	225.2
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	18700	19300	19800	20400	21500	22000	22700	23400	24000

Printed on 4/23/2024 5:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..