

EARTHMAX SR 475 - Ladda ned faktablad



Description

EARTHMAX SR 475 är ett radialdäck helt i stål som är särskilt konstruerat för långtradare utan midjestyning. Det passar perfekt till hårda och steniga underlag, i synnerhet vid långa transporter. Det unika däcktönstret genererar mindre värme i varma klimat och erbjuder utmärkt dragförmåga. Den kraftfulla stålradialstommen med stålbalten ger imponerande stabilitet och motståndskraft mot revor och punkteringar. EARTHMAX SR 475 är konstruerat med en fyrkantig däcksuldra som säkerställer utmärkt manövreringsförmåga och hantering samt maximerar kontakten med underlaget.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
18.00 R 33	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5		490	1860	860	5721	TL	265
18.00 R 33	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		490	1860	860	5721	TL	265
18.00 R 33	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		490	1860	860	5721	TL	292
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		654	2160	971	6589	TL	355
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5		654	2160	971	6589	TL	422

Printed on 4/13/2024 8:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..