

## EARTHMAX SR 475 - Ladda ned faktablad



### Description

EARTHMAX SR 475 är ett radialdäck helt i stål som är särskilt konstruerat för långtradare utan midjestyning. Det passar perfekt till hårda och steniga underlag, i synnerhet vid långa transporter. Det unika däcktönstret genererar mindre värme i varma klimat och erbjuder utmärkt dragförmåga. Den kraftfulla stålradialstommen med stålbalten ger imponerande stabilitet och motståndskraft mot revor och punkteringar. EARTHMAX SR 475 är konstruerat med en fyrkantig däcksuldra som säkerställer utmärkt manövreringsförmåga och hantering samt maximerar kontakten med underlaget.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94064397	E4	**	191 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	182
18.00 R 33	CUT RESISTANT COMPOUND	94064854	E4	***	195 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	182
18.00 R 33	STANDARD COMPOUND	94064861	E4	***	195 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	200
24.00 R 35	CUT RESISTANT COMPOUND	94066933	E4	**	209 B	17.00/3.5		25.7	85	38.2	259.4	TL	243
24.00 R 35	STANDARD COMPOUND	94066940	E4	**	209 B	17.00/3.5		25.7	85	38.2	259.4	TL	289

Printed on 4/23/2024 5:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..