

EARTHMAX SR 47 - Tekniska specifikationer



Description

EARTHMAX SR 47 (E-4) är ett stålradialdäck för gruvtruckar som används i miljöer med högsta tänkbara krav på skydd mot punktering och skärskador från stenar. Mönsterdjupet och den unika mönsterdesignen ger E-4 hög slitstyrka även vid längre transporter, vilket minskar stilleståndstiden och ökar produktiviteten. Tillgängligt med standardgummiblandning och gummiblandning med hög motståndskraft mot skärskador.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions US Standard

Usa code	94064472
TMPH	140
Overall Width (inch)	20.1
Overall Diameter (inch)	74.2
Static Loaded Radius (inch)	34.1
Rolling Circumference (inch)	223.4
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	105	109	112	116
30	24700	25400	26000	26800

Printed on 2/27/2024 9:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..