

EARTHMAX SR 47 - Tekniska specifikationer



Description

EARTHMAX SR 47 (E-4) är ett stålradialdäck för gruvtruckar som används i miljöer med högsta tänkbara krav på skydd mot punktering och skärskador från stenar. Mönsterdjupet och den unika mönsterdesignen ger E-4 hög slitstyrka även vid längre transporter, vilket minskar stilleståndstiden och ökar produktiviteten. Tillgängligt med standardgummiblandning och gummiblandning med hög motståndskraft mot skärskador.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 21.00 R 33 |
| LI/SS | 200 B |

Dimensions International Standard

| | |
|----------------------------|-----------|
| TKPH | 227 |
| Overall Width (mm) | 575 |
| Overall Diameter (mm) | 2001 |
| Static Loaded Radius (mm) | 918 |
| Rolling Circumference (mm) | 6113 |
| Rim Rec | 15.00/3.0 |
| Rim Alt | -- |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (Kg)

| km/h / bar | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 10900 | 11200 | 11500 | 11800 | 12500 | 12850 | 13200 | 13600 | 14000 |

Printed on 4/19/2024 1:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..