

## EARTHMAX SR 47 - Ladda ned faktablad



### Description

EARTHMAX SR 47 (E-4) är ett stålradialdäck för gruvtruckar som används i miljöer med högsta tänkbara krav på skydd mot punktering och skärskador från stenar. Mönsterdjupet och den unika mönsterdesignen ger E-4 hög slitstyrka även vid längre transporter, vilket minskar stilleståndstiden och ökar produktiviteten. Tillgängligt med standardgummiblandning och gummiblandning med hög motståndskraft mot skärskador.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94064489	E4	***	195 B	13.00/2.5		20.1	74.2	34.1	223.4	TL	115
18.00 R 33	CUT RESISTANT COMPOUND	94045815	E4	**	191 B	13.00/2.5	--	20.1	74.2	34.1	223.4	TL	115
18.00 R 33	HEAT RESISTANT	94070190	E4	**	191 B	13.00/2.5	--	20.1	74.2	34.1	223.4	TL	156
18.00 R 33	STANDARD COMPOUND	94064472	E4	***	195 B	13.00/2.5		20.1	74.2	34.1	223.4	TL	140
18.00 R 33	STANDARD COMPOUND	94046102	E4	**	191 B	13.00/2.5	--	20.1	74.2	34.1	223.4	TL	140
21.00 R 33	CUT RESISTANT COMPOUND	94057801	E4	**	200 B	15.00/3.0	--	22.6	78.8	36.1	240.7	TL	155
21.00 R 33	STANDARD COMPOUND	94057788	E4	**	200 B	15.00/3.0	--	22.6	78.8	36.1	240.7	TL	185
21.00 R 35	CUT RESISTANT COMPOUND	94064380	E4	**	201 B	15.00/3.0	17.00/3.0	23	80.5	37.2	248.5	TL	179
21.00 R 35	HEAT RESISTANT COMPOUND	94069842	E4	**	201 B	15.00/3.0	17.00/3.0	23	80.5	37.2	248.5	TL	243
21.00 R 35	STANDARD COMPOUND	94065288	E4	**	201 B	15.00/3.0	17.00/3.0	23	80.5	37.2	248.5	TL	209
24.00 R 35	CUT RESISTANT COMPOUND	94041244	E4	**	209 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	182
24.00 R 35	CUT RESISTANT COMPOUND	94060917	E4	***	212 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	182
24.00 R 35	STANDARD COMPOUND	94041251	E4	**	209 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	216
24.00 R 35	STANDARD COMPOUND	94060924	E4	***	212 B	17.00/3.5	--	26.4	85.9	38.7	258.5	TL	216

Printed on 2/27/2024 8:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..