

EARTHMAX SR 48 - Tekniska specifikationer



Description

EARTHMAX SR 48 är ett radialdäck helt i stål som är särskilt framtaget och konstruerat för lastbilar. Det ger förbättrad dragförmåga och utomordentlig mönsterslitstyrka, även i de mest krävande och steniga användningsmiljöer. Däcket är idealiskt för tung last. Däckskuldrans fyrkantiga design skyddar sidoväggen mot skärskador och andra skador. EARTHMAX SR 48 har en stark stålradialstomme som ger exceptionellt skydd mot stötar och stenperforering, och därmed ökad produktivitet.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions International Standard

TKPH	377
Overall Width (mm)	665
Overall Diameter (mm)	2180
Static Loaded Radius (mm)	993
Rolling Circumference (mm)	6621
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4
Tread Depth	58

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..