

EARTHMAX SR 48 - Tekniska specifikationer



Description

EARTHMAX SR 48 är ett radialdäck helt i stål som är särskilt framtaget och konstruerat för lastbilar. Det ger förbättrad dragförmåga och utomordentlig mönsterslitstyrka, även i de mest krävande och steniga användningsmiljöer. Däcket är idealiskt för tung last. Däckskuldrans fyrkantiga design skyddar sidoväggen mot skärskador och andra skador. EARTHMAX SR 48 har en stark stålradialstomme som ger exceptionellt skydd mot stötar och stenperforering, och därmed ökad produktivitet.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions US Standard

Usa code	94053209
TMPH	301
Overall Width (inch)	29.1
Overall Diameter (inch)	105.8
Static Loaded Radius (inch)	48.2
Rolling Circumference (inch)	321.5
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4
Tread Depth	86

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..