

EARTHMAX SR 49 - Tekniska specifikationer



Description

EARTHMAX SR 49 är ett radialdäck helt i stål som är konstruerat för hjullastare och bandschaktare, dumpers med lågprofil samt gruvlastmaskiner. EARTHMAX SR 49 ger optimal prestanda vid tuffa gruvdriftsarbeten som kräver enastående dragförmåga och stabilitet. Däcket har ett riktat mönster och är tillverkat av en speciell gummiblandning med skärmotstånd som ger utmärkt hållbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Gruvlastmaskin • Hjullastare • Dumper med lågprofil

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33

Dimensions International Standard

Overall Width (mm)	899
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	890
Rolling Circumference (mm)	6125
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****
TRA Code	E4

Load capacity (Kg)

km/h / bar

* "consult your servicing dealer or BKT representative for speed, load and pressure details."

Printed on 4/13/2024 8:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..