

EARTHMAX SR 49 - Ladda ned faktablad



Description

EARTHMAX SR 49 är ett radialdäck helt i stål som är konstruerat för hjullastare och bandschaktare, dumpers med lågprofil samt gruvlastmaskiner. EARTHMAX SR 49 ger optimal prestanda vid tuffa gruvdriftsarbeten som kräver enastående dragförmåga och stabilitet. Däcket har ett riktat mönster och är tillverkat av en speciell gummiblandning med skärmotstånd som ger utmärkt hållbarhet.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Gruvlastmaskin • Hjullastare • Dumper med lågprofil

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
35/65 R 33	CUT RESISTANT COMPOUND	94057115	L4	***	229 A2	28.00/3.5	--	35.4	81.1	35	241.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94057108	E4/L4	****/***		28.00/3.5	--	35.4	81.1	35	241.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94045082	L4	**	224 A2	28.00/3.5	--	35.4	81.1	35	241.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94051939	E4	****		28.00/3.5	--	35.4	81.1	35	241.1	TL
45/65 R 45	CUT RESISTANT COMPOUND	94067572	L4	**	245 A2	36.00/4.5		44.5	107.5	46.9	319.4	TL

Printed on 4/20/2024 5:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..