# EARTHMAX SR 50 - Tekniska specifikationer

## Description

EARTHMAX SR 50 (L-5) är ett stålradialdäck för hjullastare. Det pålitliga höljet och sidoväggsskydden gör det här däcket idealiskt för de mest krävande jobben. EARTHMAX SR 50 är tillverkat av en speciell skärtålig gummiblandning som ger däcket en lång livslängd. Förarna uppskattar dessutom däckets utomordentliga dragkraft och stabilitet, och den bekväma körningen.

## UM

US Standard

## Construction

RADIAL

## Machinery

OTR: Hjullastare

| | |
|---|---|
| **Version** | CUT RESISTANT COMPOUND |
| **Type** | TL |
| **Tyre Size** | 29.5 R 25 |
| **LI/SS** | 208 A2 |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94037230 |
| **Overall Width (inch)** | 30.5 |
| **Overall Diameter (inch)** | 74.8 |
| **Static Loaded Radius (inch)** | 33.9 |
| **Rolling Circumference (inch)** | 225.3 |
| **Rim Rec** | 25.00/3.5 |
| **Star Rating** | * |
| **TRA Code** | L5 |

## Load capacity (lbs)

| mph / psi | 58 | 62 | 65 | 69 | 73 |
|---|---|---|---|---|---|
| **5** | 34200 | 35300 | 37500 | 38600 | 39700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 4:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..