

EARTHMAX SR 50 - Ladda ned faktablad



Description

EARTHMAX SR 50 (L-5) är ett stålradialdäck för hjullastare. Det pålitliga höljet och sidoväggsskydden gör det här däckets idealiskt för de mest krävande jobben. EARTHMAX SR 50 är tillverkat av en speciell skärtålig gummiblandning som ger däckets en lång livslängd. Förarna uppskattar dessutom däckets utomordentliga dragkraft och stabilitet, och den bekväma körningen.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Hjullastare

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 R 25	CUT RESISTANT COMPOUND	L5	*	202 A2	22.00/3.0		690	1772	806	5334	TL
26.5 R 25	CUT RESISTANT COMPOUND	L5	**	209 A2	22.00/3.0		690	1772	806	5334	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5	*	208 A2	25.00/3.5		775	1901	862	5722	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5	**	216 A2	25.00/3.5		775	1901	862	5722	TL

Printed on 4/24/2024 7:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..