

EARTHMAX SR 53 - Tekniska specifikationer



Description

EARTHMAX SR 53 M är ett radialdäck helt i stål som är specialdesignat för hjullastare eller bandschaktare, dumpers med lågprofil och gruvlastmaskiner som körs i krävande, steniga förhållanden, bland annat i underjordisk drift och på skrotupplag. Det djupa mönstret hos L-5 och gummiblandningen med stor motståndskraft mot skärande underlag ger längre livslängd i kombination med utmärkt dragförmåga och stabilitet.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Hjullastare • Dumper med lågprofil

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	35/65 R 33

Dimensions International Standard

Overall Width (mm)	910
Overall Diameter (mm)	2063
Static Loaded Radius (mm)	915
Rolling Circumference (mm)	6215
Rim Rec	28.00/3.5
Star Rating	**
TRA Code	L5

Load capacity (Kg)

* "consult your servicing dealer or BKT representative for load and pressure details."

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 6:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..