

## EARTHMAX SR 53 - Tekniska specifikationer



### Description

EARTHMAX SR 53 M är ett radialdäck helt i stål som är specialdesignat för hjullastare eller bandschaktare, dumpers med lågprofil och gruvlastmaskiner som körs i krävande, steniga förhållanden, bland annat i underjordisk drift och på skrotupplag. Det djupa mönstret hos L-5 och gummiblandningen med stor motståndskraft mot skärande underlag ger längre livslängd i kombination med utmärkt dragförmåga och stabilitet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Bulldozer • Hjullastare • Dumper med lågprofil

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	50/65 R 51
LI/SS	253 A2

## Dimensions US Standard

Usa code	94068913
Overall Width (inch)	48.8
Overall Diameter (inch)	121.7
Static Loaded Radius (inch)	54
Rolling Circumference (inch)	366.5
Rim Rec	40.00/4.5
Star Rating	**
TRA Code	L5

## Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	123500	128000	132500	135500	139000	143500

Printed on 4/23/2024 11:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..