

## EARTHMAX SR 55 - Tekniska specifikationer



### Description

EARTHMAX SR 55 M är ett radialdäck helt i stål som är specialdesignat för hjullastare, bandschaktare och dumpers med lågprofil som körs i de mest krävande stenbrotts- och gruvdriftsmiljöerna samt på skrotupplag. Tack vare det utmärkta skyddet mot revor som uppnås med ett extra djupt och slätt mönster kan EARTHMAX SR 55 erbjuda förstklassig produktivitet med minskade driftstopp kombinerat med utmärkt hållbarhet. Maskinoperatörer lär också uppskatta den extraordinära stabiliteten och dragförmågan.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Bulldozer • Gruvlastmaskin • Hjullastare

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 35/65 R 33             |
| LI/SS     | 229 A2                 |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Overall Width (mm)         | 900       |
| Overall Diameter (mm)      | 2065      |
| Static Loaded Radius (mm)  | 915       |
| Rolling Circumference (mm) | 6175      |
| Rim Rec                    | 28.00/3.5 |
| Rim Alt                    | --        |
| Star Rating                | ***       |
| TRA Code                   | L5S       |

## Load capacity (Kg)

| km/h / bar | 6.75  | 7.00  | 7.25  | 7.50  | 7.75  | 8.00  |
|------------|-------|-------|-------|-------|-------|-------|
| 10         | 29000 | 30000 | 30750 | 31500 | 32000 | 32500 |

Printed on 4/15/2024 11:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..