

EARTHMAX SR 57 - Tekniska specifikationer



Description

EARTHMAX SR 57 är ett radialdäck helt i stål som är specialdesignat för hjullastare, bandschaktare och anläggningsfordon som används i underjordisk gruvdrift. Däcket ger överlägsen dragförmåga, stabilitet och komfort på krävande och steniga underlag. Det extra djupa mönstret hos L-5 och den specialkomponerade UMS-gummiblandningen för underjordisk gruvdrift ger längre hållbarhet samt extraordinär motståndskraft mot revor och punkteringar orsakade av sten.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Gruvlastmaskin • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	8.25 R 15

Dimensions US Standard

Usa code	94052783
Overall Width (inch)	9.4
Overall Diameter (inch)	34.6
Rim Rec	6.50
Rim Alt	7.00
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	102
3.7	6560

Printed on 4/23/2024 4:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..