

EARTHMAX SR 57 - Ladda ned faktablad



Description

EARTHMAX SR 57 är ett radialdäck helt i stål som är specialdesignat för hjullastare, bandschaktare och anläggningsfordon som används i underjordisk gruvdrift. Däcket ger överlägsen dragförmåga, stabilitet och komfort på krävande och steniga underlag. Det extra djupa mönstret hos L-5 och den specialkomponerade UMS-gummiblandningen för underjordisk gruvdrift ger längre hållbarhet samt extraordinär motståndskraft mot revor och punkteringar orsakade av sten.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Gruvlastmaskin • Hjullastare

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	Type
10.00 R 15	CUT RESISTANT COMPOUND	L5	*		7.50	7.00	278	916	TT
7.50 R 15	CUT RESISTANT COMPOUND	L5	*		6.00	6.5	223	845	TT
8.25 R 15	CUT RESISTANT COMPOUND	L5	*		6.50	7.00	240	880	TT
10.00 R 20	CUT RESISTANT COMPOUND	L5	*		7.5		272	1105	TT
12.00 R 20	CUT RESISTANT COMPOUND	L5	*		8.50		318	1180	TT
18.00 R 25	CUT RESISTANT COMPOUND	L5	**	204 A2	13.00/2.5		515	1651	TL

Printed on 4/23/2024 8:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..