

EARTHMAX SR LOADER - Tekniska specifikationer



Description

EARTHMAX SR LOADER är ett terrängdäck speciellt utformat för lastning och schaktning samt för transportarbeten med ramstyrda dumprar. Dess stålradialstomme som är förstärkt med stålbalten i flera lager och den unika gummiblandningen ger utmärkt motståndskraft mot revor och punkteringar samt längre livslängd. EARTHMAX SR LOADER har ett unikt däckmönster med självrensande egenskaper och ger utmärkt dragförmåga på flera typer av terräng.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

Dimensions US Standard

Usa code	94064847
TMPH	158
Overall Width (inch)	26.8
Overall Diameter (inch)	68.3
Static Loaded Radius (inch)	30
Rolling Circumference (inch)	203.9
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400
5	28300	29100	30900	32000	33100	-

Printed on 4/24/2024 9:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..