

EM 933 SUPER - Tekniska specifikationer



Description

EM 933 SUPER har utformats speciellt för grävmaskiner i grävnings- och lastningstillämpningar. Den unika sidoväggsutformningen med en utskjutande kant möjliggör nära kontakt mellan två däck vilket eliminerar behovet av den gummiring som förhindrar stenpenetration. Det unika däcktönstret ger en överlägsen dragkraft vid tuffa förhållande. EM 933 SUPER-däcket har även enastående körkomfort och förbättrade självrensande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Grävmaskin

Version	STANDARD
Type	TT
Tyre Size	290/90 - 20
LI/SS	152 B / 168 A2

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	295
Overall Diameter (mm)	1055
Rim Rec	8.00
TRA Code	E2

Load capacity (Kg)

	km/h / bar	9.00
	10	5600
	50	3530

Printed on 3/4/2024 11:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..