

## EM 936 LOADER SPECIAL - Tekniska specifikationer



### Description

EM 936 LOADER SPECIAL är ett däck för teleskoplastare som används för lastning. Det har utomordentlig åkkomfort och förbättrade självrensande egenskaper. Det har dessutom hög körkomfort och utmärkt dragkraft även under svåra arbetsförhållanden.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Hjullastare • Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20 (405/70 - 20)
LI/SS	149 B

## Dimensions International Standard

Ply Rating	14
Overall Width (mm)	405
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3295
Rim Rec	13 SDC
Rim Alt	13
TRA Code	E2

## Load capacity (Kg)

km/h / bar	3.50
50	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/5/2024 7:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..