

EM 936 SUPER - Tekniska specifikationer



Description

EM 936 SUPER är speciellt utformat för grävmaskiner och teleskoplastare vid grävning och lastning samt transporttillämpningar. Med en ökad spårbredd på 8-10 % erbjuder EM 936 SUPER enastående stabilitet och förbättrad körkomfort. Det garanterar också en hög nivå av hanteringskomfort och ger utmärkt dragkraft även under tunga serviceförhållanden.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Grävmaskin

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions US Standard

Usa code	94062690
Ply Rating	16
Section Width (inch)	10.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	131.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	108
30	6600

Printed on 4/25/2024 9:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..