

## EM 936 SUPER - Ladda ned faktablad



### Description

EM 936 SUPER är speciellt utformat för grävmaskiner och teleskoplastare vid grävning och lastning samt transporttillämpningar. Med en ökad spårbredd på 8-10 % erbjuder EM 936 SUPER enastående stabilitet och förbättrad körkomfort. Det garanterar också en hög nivå av hanteringskomfort och ger utmärkt dragkraft även under tunga serviceförhållanden.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Grävmaskin

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
10.00 - 20	STANDARD	E2	145 B	14	7.5	7.0 ; 8.0	277	1080	500	3336	TT
10.00 - 20	STANDARD	E2	146 B	16	7.5	7.0 ; 8.0	277	1080	500	3336	TT

Printed on 4/25/2024 9:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..