

EM 936 - Tekniska specifikationer



Description

EM 936 är ett däck för grävmaskiner och teleskoplastare som används för grävarbeten och lastning. En av storlekarna passar dessutom utmärkt för väghyvlar och hjullastare som används för hyvling, lastning och transporter. EM 936 har utomordentlig åkkomfort och förbättrade självrensande egenskaper. Det har dessutom hög körkomfort och utmärkt dragkraft även under svåra arbetsförhållanden. Specialversionen är tillverkad av en speciell gummiblandning.

UM

US Standard

Construction

❖ BIAS

Machinery

Industri: Grävmaskin • Teleskoplastare

| | |
|-----------|-----------|
| Version | DUAL BEAD |
| Type | TL |
| Tyre Size | 17.5 - 25 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94066643 |
| Ply Rating | 24 |
| Overall Width (inch) | 17.7 |
| Overall Diameter (inch) | 52.8 |
| Static Loaded Radius (inch) | 23.6 |
| Rolling Circumference (inch) | 159.8 |
| Rim Rec | 14.00/1.5 |
| TRA Code | E2/L2 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 102 |
| 5 | 22045 |

Printed on 4/20/2024 12:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..