

## EM 937 IND3 (ECH) - Tekniska specifikationer



### Description

EM 937 (E-3) IND är avsett för utrustning som hanterar tomma containrar vid stapling och lastning. Det är mycket pålitligt och har lång livslängd. EM 937 (E-3) IND är idealiskt på stenbelagda ytor och för all användning som kräver en hög grad av manövrering i hamnen. \*For size 14.00-24 please confirm service rim or consult manufacturer/distributor

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Tomcontainerhanterare

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

## Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4050
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND3

## Load capacity (Kg)

km/h / bar	10.00
10	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 1:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..