

EM 937 IND3 (ECH) - Ladda ned faktablad



Description

EM 937 (E-3) IND är avsett för utrustning som hanterar tomma containrar vid stapling och lastning. Det är mycket pålitligt och har lång livslängd. EM 937 (E-3) IND är idealiskt på stenbelagda ytor och för all användning som kräver en hög grad av manövrering i hamnen. *For size 14.00-24 please confirm service rim or consult manufacturer/distributor

UM

International Standard

Construction

 BIAS

Machinery

Industri: Tomcontainerhanterare

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 24	PORT INDUSTRIAL	IND3	28	10.00 W		375	1368	628	4050	TT
14.00 - 24	PORT INDUSTRIAL	IND3	28	10.00 W		375	1368	628	4050	TL
14.00 - 24	PORT INDUSTRIAL	IND3	28	10.00 WA	10.00 VA	375	1368	628	4050	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 1:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..