

EM 938 - Ladda ned faktablad



Description

EM 938 är avsett för användning på grävmaskiner vid vägbyggen. Den speciella gummiblandningen i slitbanan gör däckets extra tåligt mot skärskador och revor, och det aggressiva slitbanemönstret ger utmärkt dragkraft. EM 938 har utomordentliga självrensande egenskaper. Det kraftiga höljet ger ett extra gott skydd mot stötar även vid tunga arbeten.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Grävmaskin

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	0	OD	SLR	RC	Type
9.00 - 20	STANDARD	94064625	E2		16	7.0	6.5 ; 7.5	10.1	39.8	18.9	120.9	TT
9.00 - 20	STANDARD	94046034	E2	140 B	14	7.0	6.5 ; 7.5	10.1	39.8	18.9	120.9	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/24/2025 8:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..