

F 240 - Tekniska specifikationer



Description

F 240 är ett skogsdäck för avverkningsarbeten. Slitbanemönstret ger goda styregenskaper och utmärkt dragkraft, och har utomordentliga självrensande egenskaper. Den överlägsna gummiblandningen i slitbanan ger ett utomordentligt skydd mot skärskador och slitage för att ge däckets en längre livslängd. Den stora kontaktytan ger F 240 bättre stabilitet.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Lunnare

Version	STANDARD
Type	TT
Tyre Size	18 - 15.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	450
Overall Diameter (mm)	990
Static Loaded Radius (mm)	430
Rolling Circumference (mm)	2930
Rim Rec	AG 13.00
ECE	E11-106R-004259
TRA Code	LS2

Load capacity (Kg)

km/h / bar	3.50
30	4185

Printed on 4/23/2024 9:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..