

FARM 2000 PLUS - Tekniska specifikationer



Description

FARM 2000 PLUS är ett lantbruksdäck med ett högre antal däckklackar för bättre prestanda på åkern. Det djupa mönstret ger däckets längre livslängd och utmärkt dragförmåga, samtidigt som den överlägsna gummiblandningen är en garanti för bättre motståndskraft mot skärande underlag och punkteringar. FARM 2000 PLUS uppvisar utmärkta självrensande egenskaper och specialdesignade däckklacksvinklar gör att däckets lämpar sig särskilt väl för åker- och transportarbeten.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1435
Static Loaded Radius (mm)	657
Rolling Circumference (mm)	4311
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 4/19/2024 8:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..