

FARM 2000 - Tekniska specifikationer



Description

Däcket FARM 2000 är lämpligt på traktorer för markbearbetning. Det har designats med en speciell skär- och flisbeständig sammansättning för att säkerställa bättre hållbarhet. Tack vare sitt starka hölje erbjuder FARM 2000 en hög lastkapacitet. Det tillhandahåller också bra dragkrafter och självrengörande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

Dimensions International Standard

Section Width (mm)	265
Overall Diameter (mm)	775
Static Loaded Radius (mm)	349
Rolling Circumference (mm)	2294
SRI (mm)	360
Rim Rec	9.00
ECE	E11-106R-003516

Load capacity (Kg)

	km/h / bar	3.60
	10 FR	2380
	25 FR	2025
	30 FR	1905
	40 FR	1700
	10 DW	1650
	25 DW	1405
	30 DW	1320
	40 DW	1180

Printed on 4/25/2024 7:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..