

FARM 2000 - Tekniska specifikationer



Description

Däcket FARM 2000 är lämpligt på traktorer för markbearbetning. Det har designats med en speciell skär- och flisbeständig sammansättning för att säkerställa bättre hållbarhet. Tack vare sitt starka hölje erbjuder FARM 2000 en hög lastkapacitet. Det tillhandahåller också bra dragkrafter och självrengörande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 8.3 - 20 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 4 |
| Section Width (mm) | 210 |
| Overall Diameter (mm) | 895 |
| Static Loaded Radius (mm) | 431 |
| Rolling Circumference (mm) | 2714 |
| Rim Rec | W 7 |
| ECE | E11-106R-004369 |
| TRA Code | R1 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 1.60 |
| 30 | 560 |

Printed on 4/25/2024 8:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..