

## FARM HIGHWAY TOUGH - Tekniska specifikationer



### Description

FARM HIGHWAY TOUGH är ett höghastighetsdäck som är avsett för transport- och jordbearbetningstillämpningar med släpvagnar och arbetsfordon. Det ger hög lastkapacitet även vid höga hastigheter vilket säkerställer lång livslängd för däck.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Släpvagn

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 11L - 15 FI |
| LI/SS     | 128 J       |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 12              |
| Section Width (mm)         | 279             |
| Overall Diameter (mm)      | 777             |
| Static Loaded Radius (mm)  | 347             |
| Rolling Circumference (mm) | 2214            |
| Rim Rec                    | 8 LB            |
| Rim Alt                    | 10 LB ; 8 J     |
| ECE                        | E11-54R-0017871 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 6.20 |
| 100        | 1800 |

Printed on 4/26/2024 12:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..