

## FARM HIGHWAY TOUGH - Tekniska specifikationer



### Description

FARM HIGHWAY TOUGH är ett höghastighetsdäck som är avsett för transport- och jordbearbetningstillämpningar med släpvagnar och arbetsfordon. Det ger hög lastkapacitet även vid höga hastigheter vilket säkerställer lång livslängd för däck.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	11L - 15 FI
LI/SS	120 J

## Dimensions US Standard

Usa code	94039937
Ply Rating	8
Section Width (inch)	11
Overall Diameter (inch)	30.6
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	87.2
Rim Rec	8 LB
Rim Alt	10 LB ; 8 J
ECE	E11-54R-0018902

## Load capacity (lbs)

mph / psi	60
62	3080

Printed on 4/26/2024 7:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..