

FARM SPECIAL - Tekniska specifikationer



Description

FARM SPECIAL är ett traktordäck som lämpar sig för jordbearbetning. Det kraftfulla däckhöljet erbjuder hög motståndskraft mot punkteringar och längre livslängd, samtidigt som de rundade skuldrorna motverkar skador på marken och skyddar värdefulla grödor. FARM SPECIAL har ett unikt mönster med speciella lerbrytare för maximal självrensande effekt. Dessutom ger dubbla, vinklade däckklackar utmärkt dragförmåga och minskar slirning.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 24
LI/SS	120 A8

Dimensions US Standard

Usa code	94060702
Ply Rating	8
Section Width (inch)	13.8
Overall Diameter (inch)	47.4
Static Loaded Radius (inch)	21.8
Rolling Circumference (inch)	143.1
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-005530
TRA Code	R1

Load capacity (lbs)

mph / psi	28
25	3080

Printed on 12/11/2023 11:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..