

## FARM SPECIAL - Tekniska specifikationer



### Description

FARM SPECIAL är ett traktordäck som lämpar sig för jordbearbetning. Det kraftfulla däcksölet erbjuder hög motståndskraft mot punkteringar och längre livslängd, samtidigt som de rundade skuldrorna motverkar skador på marken och skyddar värdefulla grödor. FARM SPECIAL har ett unikt mönster med speciella lerbrytare för maximal självrensande effekt. Dessutom ger dubbla, vinklade däcksölar utmärkt dragförmåga och minskar slirning.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	139 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	451
Overall Diameter (mm)	1533
Static Loaded Radius (mm)	689
Rolling Circumference (mm)	4599
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-005537
TRA Code	R1

## Load capacity (Kg)

km/h / bar	1.40
30	2430

Printed on 4/27/2024 1:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..