

FL 252 - Tekniska specifikationer



Description

FL 252 är ett däck för höskörd med rotorvändare/strängvändare. Det passar även för gaffeltruckar som används för logistiktillämpningar. Däcket är mycket pålitligt och det speciella slitbanemönstret ger maximal stabilitet vid lyft.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Roterande harv
Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions International Standard

Ply Rating	10
Section Width (mm)	170
Overall Diameter (mm)	550
Rim Rec	4.00 E

Load capacity (Kg)

km/h / bar	8.50
25 LOAD WHEEL	1715
25 STEER WHEEL	1320
10 OTHER VEHICLES	1715
25 OTHER VEHICLES	1320
STATIC SIDE LOADER	1995

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/8/2024 3:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..