

FL 252 - Tekniska specifikationer



Description

FL 252 är ett däck för höskörd med rotorvändare/strängvändare. Det passar även för gaffeltruckar som används för logistik tillämpningar. Däcket är mycket pålitligt och det speciella slitbanemönstret ger maximal stabilitet vid lyft.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Roterande harv
Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions US Standard

Usa code	94006854
Ply Rating	10
Section Width (inch)	6.7
Overall Diameter (inch)	21.7
Rim Rec	4.00 E

Load capacity (lbs)

mph / psi	123
15 LOAD WHEEL	3780
15 STEER WHEEL	2910
5 OTHER VEHICLES	3780
15 OTHER VEHICLES	2910
STATIC SIDE LOADER	4400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/6/2024 4:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..