

FL 630 SUPER - Tekniska specifikationer



Description

FL 630 SUPER är ett flotationsdäck lämpligt för fält- och vägtillämpningar med släpvagnar, tankbilar och spridare. Den resistent strukturen ger utmärkt dragkraft och perfekt grepp även i kurvor och vid manövrering, medan en förstärkt kula och stålremmen säkerställer förbättrad hållbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Spridare • Tankbil • Släpvagn

Version	HD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	178 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4292
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E11-106R-003006

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	1875	2325	2775	3375	3900	4500	5100	5475	6075	6675	7050	7500
50	2270	2815	3360	4085	4720	5445	6175	6625	7355	8080	8535	9075
40	2550	3165	3775	4590	5305	6120	6940	7450	8265	9080	9590	10200
30	2835	3515	4195	5100	5890	6795	7705	8270	9175	10080	10650	11325
25	2965	3675	4385	5335	6165	7110	8060	8655	9600	10550	11140	11850
10	3375	4185	4995	6075	7020	8100	9180	9855	10935	12015	126960	13500

Printed on 4/20/2024 6:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..