

FL 630 SUPER - Tekniska specifikationer



Description

FL 630 SUPER är ett flotationsdäck lämpligt för fält- och vägtillämpningar med släpvagnar, tankbilar och spridare. Den resistent strukturen ger utmärkt dragkraft och perfekt grepp även i kurvor och vid manövrering, medan en förstärkt kula och stålremmen säkerställer förbättrad hållbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Spridare • Tankbil • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	169 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4258
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E4-106R-000806

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1690	1955	2220	2695	3120	3595	4070	4385	4860	5280
65	1860	2150	2440	2960	3425	3945	4470	4815	5340	5800
50	2250	2600	2950	3585	4145	4775	5410	5830	6460	7020
40	2525	2920	3315	4025	4660	5370	6080	6550	7260	7890
25	2935	3395	3850	4675	5410	6235	7060	7610	8435	9165
10	3345	3865	4385	5385	6160	7100	8040	8670	9605	10440

Printed on 4/23/2024 1:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..