# FL 630 SUPER - Ladda ned faktablad

## Description

FL 630 SUPER är ett flotationsdäck lämpligt för fält- och vägtillämpningar med släpvagnar, tankbilar och spridare. Den resistenta strukturen ger utmärkt dragkraft och perfekt grepp även i kurvor och vid manövrering, medan en förstärkt kula och stålremmen säkerställer förbättrad hållbarhet.

## UM

International Standard

## Construction

RADIAL

## Machinery

Lantbruk: Spridare • Tankbil • Släpvagn

| SIZE | Version | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **560/60 R 22.5** | STANDARD | 161 D | | | AG 16.00 | 17.00 ; 20.00 | 543 | 1244 | 549 | 3785 | 600 | TL | E4-106R-000794 |
| **560/60 R 22.5** | STANDARD | 165 D | | | AG 16.00 | 17.00 ; 20.00 | 543 | 1244 | 549 | 3785 | 600 | TL | E11-106R-006945 |
| **580/65 R 22.5** | STANDARD | 166 D | | | AG 18.00 | AG 16.00 ; AG 17.00 ; AG 20.00 | 577 | 1326 | 594 | 4058 | 625 | TL | E4-106R-001416 |
| **580/65 R 22.5** | STANDARD | 174 D | 174 D | 174 D | AG 18.00 | AG 16.00 ; AG 17.00 ; AG 20.00 | 582 | 1326 | 594 | 4058 | 625 | TL | E11-106R-008289 |
| **600/50 R 22.5** | STANDARD | 159 D | | | AG 20.00 | | 611 | 1170 | 518 | 3533 | 550 | TL | E11-106R-005992 |
| **600/55 R 22.5** | STANDARD | 162 D | | | AG 20.00 | | 595 | 1232 | 560 | 3757 | 575 | TL | E11-106R-004759 |
| **600/55 R 26.5** | HD | 177 D | | | AG 20.00 | | 611 | 1333 | 604 | 4104 | 625 | TL | E11-106R-003005 |
| **600/55 R 26.5** | STANDARD | 165 D | | | AG 20.00 | | 611 | 1333 | 606 | 4078 | 625 | TL | E4-106R-001414 |
| **650/55 R 26.5** | HD | 178 D | | | AG 20.00 | | 645 | 1389 | 628 | 4292 | 650 | TL | E11-106R-003006 |
| **650/55 R 26.5** | STANDARD | 169 D | | | AG 20.00 | | 645 | 1389 | 627 | 4258 | 650 | TL | E4-106R-000806 |
| **650/65 R 26.5** | STANDARD | 174 D | | | AG 20.00 | | 645 | 1519 | 684 | 4653 | 725 | TL | E4-106R-001651 |
| **710/50 R 26.5** | STANDARD | 170 D | | | AG 24.00 | AG 20.00 | 727 | 1383 | 626 | 4237 | 650 | TL | E11-106R-003009 |
| **750/45 R 26.5** | STANDARD | 170 D | | | AG 24.00 | | 754 | 1349 | 606 | 4147 | 650 | TL | E4-106R-001652 |
| **750/60 R 26.5** | STANDARD | 180 D | | | AG 24.00 | | 754 | 1574 | 694 | 4800 | 725 | TL | E4-106R-001427 |
| **650/65 R 30.5** | STANDARD | 176 D | | | AG 20.00 | | 645 | 1621 | 734 | 4976 | 775 | TL | E4-106R-001653 |
| **750/60 R 30.5** | STANDARD | 181 D | | | AG 24.00 | | 754 | 1675 | 746 | 5115 | 800 | TL | E4-106R-001499 |
| **850/50 R 30.5** | STANDARD | 182 D | 182 D | 182 D | AG 28.00 | | 860 | 1625 | 722 | 4895 | 775 | TL | E11-106R-008232 |

Printed on 4/20/2024 9:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..