

## FL 630 SUPER - Ladda ned faktablad



### Description

FL 630 SUPER är ett flotationsdäck lämpligt för fält- och vägtillämpningar med släpvagnar, tankbilar och spridare. Den resistent strukturen ger utmärkt dragkraft och perfekt grepp även i kurvor och vid manövrering, medan en förstärkt kula och stålremmen säkerställer förbättrad hållbarhet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Spridare • Tankbil • Släpvagn

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
560/60 R 22.5	STANDARD	161 D			AG 16.00	17.00 ; 20.00	543	1244	549	3785	600	TL	E4-106R-000794
560/60 R 22.5	STANDARD	165 D			AG 16.00	17.00 ; 20.00	543	1244	549	3785	600	TL	E11-106R-006945
580/65 R 22.5	STANDARD	166 D			AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	577	1326	594	4058	625	TL	E4-106R-001416
580/65 R 22.5	STANDARD	174 D	174 D	174 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	582	1326	594	4058	625	TL	E11-106R-008289
600/50 R 22.5	STANDARD	159 D			AG 20.00		611	1170	518	3533	550	TL	E11-106R-005992
600/55 R 22.5	STANDARD	162 D			AG 20.00		595	1232	560	3757	575	TL	E11-106R-004759
600/55 R 26.5	HD	177 D			AG 20.00		611	1333	604	4104	625	TL	E11-106R-003005
600/55 R 26.5	STANDARD	165 D			AG 20.00		611	1333	606	4078	625	TL	E4-106R-001414
650/55 R 26.5	HD	178 D			AG 20.00		645	1389	628	4292	650	TL	E11-106R-003006
650/55 R 26.5	STANDARD	169 D			AG 20.00		645	1389	627	4258	650	TL	E4-106R-000806
650/65 R 26.5	STANDARD	174 D			AG 20.00		645	1519	684	4653	725	TL	E4-106R-001651
710/50 R 26.5	STANDARD	170 D			AG 24.00	AG 20.00	727	1383	626	4237	650	TL	E11-106R-003009
750/45 R 26.5	STANDARD	170 D			AG 24.00		754	1349	606	4147	650	TL	E4-106R-001652
750/60 R 26.5	STANDARD	180 D			AG 24.00		754	1574	694	4800	725	TL	E4-106R-001427
650/65 R 30.5	STANDARD	176 D			AG 20.00		645	1621	734	4976	775	TL	E4-106R-001653
750/60 R 30.5	STANDARD	181 D			AG 24.00		754	1675	746	5115	800	TL	E4-106R-001499
850/50 R 30.5	STANDARD	182 D	182 D	182 D	AG 28.00		860	1625	722	4895	775	TL	E11-106R-008232

Printed on 4/23/2024 12:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..