

FL 630 ULTRA - Tekniska specifikationer



Description

FL 630 ULTRA lämpar sig för släp, tankbilar och spridare. Tack vare den förstärkta vulsten och en speciell mönsterdesign är däckets ett utmärkt flerfunktionsdäck för användning på alla slags åkrar och på väg. FL 630 ULTRA minskar jordpackningen med imponerande resultat.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Spridare • Tankbil • Släpvagn

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 650/55 R 26.5 |
| LI/SS | 169 D/180 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 645 |
| Overall Diameter (mm) | 1389 |
| Static Loaded Radius (mm) | 600 |
| Rolling Circumference (mm) | 4207 |
| SRI (mm) | 650 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-006814 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 65 | 1860 | 2150 | 2440 | 2960 | 3425 | 3945 | 4470 | 4815 | 5340 | 5800 |
| 50 | 2250 | 2600 | 2950 | 3585 | 4145 | 4775 | 5410 | 5830 | 6460 | 7020 |
| 40 | 2560 | 2960 | 3360 | 4080 | 4720 | 5440 | 6160 | 6640 | 7360 | 8000 |
| 25 | 2935 | 3395 | 3850 | 4675 | 5410 | 6235 | 7060 | 7610 | 8435 | 9165 |
| 10 | 3345 | 3865 | 4385 | 5325 | 6160 | 7100 | 8040 | 8670 | 9605 | 10440 |

Printed on 12/8/2023 5:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..